

41.25"

4.75"

13.5"

4.75"

13.5"

4.75"

4.75"

4.75"

32.5"

13.5"

Note: Need to finish retouching tile for specks.

Box Contains 9 Diamondtrax Interlocking Tiles  
Tile Size: 13" x 13" x .5" thick  
Color: Slate Grey

# Diamondtrax+

## Interlocking Floor Tiles

Diamondtrax+ is a very popular design and can be used for many applications and is recommended for those who would like a solid floor with an industrial or "retro" diamond-plate look.

**Sturdy and dependable.**  
Diamondtrax+ is our most popular solid tile and is recommended for garage floors and workshops where an attractive, non-slip, solid surface is desired.

**Specifications.**

Tile Size	13.00 in (33 cm) x 13.00 in (33 cm)
Height/Thickness	0.50 in (1.3 cm)
Weight	13.5 oz (0.84 lb)
Material	Polypropylene copolymer
Resistance To	Excellent - Oil, gas & other auto fluids; Good - Acids & solvents
Temp Range	-22°F (-30°C) to 248°F (120°C)
Compression Strength	3,130 psi
Fire Rating	HB (horizontal burn)

**Installation Instructions.**

**Step 1: Preparation (Optional):**  
Clear the flooring surface of any removable objects and/or items (e.g. garbage bins, storage containers, etc.). Sweep or vacuum any excess dirt and debris off of the flooring surface.

**Step 2: Locate Your Starting Point**  
Stand in your garage and face towards your garage door. Now locate the top-left corner of your garage.

**Step 3: Installing Your First Tile**  
Place your first tile (Tile A) in the top-left corner with the pegged "male" side facing the left wall and garage door wall. Remember to leave an expansion gap between the tile and wall.

**Step 4: Installing The Next Tile**  
Working left to right, interlock Tile B with Tile A making sure that loops and pegs are facing the same direction.

**Step 5: Completing Your First Row**  
Continue with your first row until the Right Wall is reached.

**Step 6: Installing Additional Rows**  
Return to the Left Wall and repeat steps 4-5 until the first three rows are completed.

**Step 7: Installing Edges**  
Following completion of the first three rows, connect the edges to the first installed row nearest to the garage door entry. Edges are only needed between the garage door rails.

**Step 8: Positioning Your Edges**  
This step begins by closing your garage door. Gently push the first 3 rows of tile with edges attached against the garage door for a precise fit.

**Step 9: Continuing Your Floor Installation**  
Resume steps 4-5 until the Back Wall is reached. Be sure to check the alignment of your floor as you progress. Cutting may be necessary along the Back Wall to complete install.

Note: Edges may have to be cut to fit within rails.

www.swisstrax.com | (760) 347-3330  
82-579 Fleming Way #A, Indio, CA 92201

Box Contains 9 Diamondtrax Interlocking Tiles  
Tile Size: 13" x 13" x .5" thick  
Area Covered: 10.56 sq.ft. (1521 sq.in.)  
Color: Slate Grey

# Diamondtrax+

## Interlocking Floor Tiles

Retro style, modern construction.

**Applications.**

- Garages
- Showrooms
- Event Floors
- Display Pads
- Residential And Commercial Workshops

**Getfloored+**  
Transform your floor in hours.

- Do-it-Yourself Installation
- Superior Quality & Design
- 70,000 lbs. Rollover Strength
- Non-Slip When Wet
- Easy to Clean & Maintain
- UV Stabilizer Built Into Material & Color
- Chemical Resistant
- 15 Year Warranty
- Up To 19 Colors Available

**Great durability!**  
Not affected by moisture, motor oils, car fluids, most acids and solvents including Skydrol, salt, magnesium chloride, hot tires and tire marks.

**Easy installation!**  
No toxic fumes or hazardous materials. No surface preparation including acid washing. Install a complete garage within hours.

**Showcase your floor!**  
Outshine the competition - our floors are highly visible and a low maintenance alternative to epoxy floor sealant.

**Perfect flooring option!**  
Safe! Slip-resistant when wet. Keep your garage and feet dry when it rains. Comfortable to stand on! Get relief on your feet versus standing on carpet, concrete or asphalt.

www.swisstrax.com | (760) 347-3330  
82-579 Fleming Way #A, Indio, CA 92201

3.0"

13.5"